


■ Tubular cable lugs, copper
0,75 - 1000 mm²

- With or without inspection hole
- Material: Copper acc. to EN 13600
- Surface: tin plated




Cable Size mm ²	Bolt ø	Without inspection hole	With inspection hole	Dimensions mm*			
				l	a	d1	d2
0,75	M 3	NDC 0,75/3	L 0,75/3 MS	15	6	1,3	3,2
1,5	M 5	NDC 1,5/5	L 1,5/5 MS	19	6	1,8	5,3
2,5	M 5	NDC 2,5/5	L 2,5/5 MS	19	6	2,3	5,3
4	M 5	NDC 4/5	L 4/5 MS	22	8	3	5,3
6	M 6	NDC 6/6	L 6/6 MS	26	9	4	6,5
10	M 6	NDC 10/6	L 10/6 MS	28	10	4,4	6,5
16	M 8	NDC 16/8	L 16/8 MS	35	11	5,5	8,5
25	M 8	NDC 25/8	L 25/8 MS	38	12	6,8	8,5
35	M 8	NDC 35/8	L 35/8 MS	42	15	8,2	8,5
50	M 10	NDC 50/10	L 50/10 MS	50	18	9,5	10,5
70	M 10	NDC 70/10	L 70/10 MS	53	20	11,2	10,5
95	M 12	NDC 95/12	L 95/12 MS	60	22	13,4	13
120	M 12	NDC 120/12	L 120/12 MS	65	26	15	13
150	M 12	NDC 150/12	L 150/12 MS	72	30	16,5	13
185	M 16	NDC 185/16	L 185/16 MS	83	30	19	17
240	M 16	NDC 240/16	L 240/16 MS	94	35	21	17
300	M 20	NDC 300/20	L 300/20 MS	111	44	23,5	21
400	M 20	NDC 400/20	L 400/20 MS	114	44	27	21
500	M 20	NDC 500/20	L 500/20 MS	144	68	31	21
630	M 20	NDC 630/20	L 630/20 MS	144	68	34	21
800	M 20	NDC 800/20	L 800/20 MS	195	100	40	21
1000	M 20	NDC1000/20	L 1000/20 MS	200	100	44	21

* Other bolt sizes are available on request

■ Butt-connectors, copper
0,75 - 1000 mm²


- Material: Copper acc. to EN 13600
- Surface: tin plated



Cable Size mm ²	Order Reference	l	d1	Cable Size mm ²	Order Reference	l	d1
0,75	NDC 0,75 L	20	1,3	95	NDC 95 L	60	13,4
1,5	NDC 1,5 L	25	1,8	120	NDC 120 L	65	15
2,5	NDC 2,5 L	25	2,3	150	NDC 150 L	70	16,5
4	NDC 4 L	25	3	185	NDC 185 L	80	19
6	NDC 6 L	25	4	240	NDC 240 L	90	21
10	NDC 10 L	30	4,4	300	NDC 300 L	100	23,5
16	NDC 16 L	35	5,5	400	NDC 400 L	110	27
25	NDC 25 L	40	6,8	500	NDC 500 L	140	31
35	NDC 35 L	45	8,2	630	NDC 630 L	160	34
50	NDC 50 L	50	9,5	800	NDC 800 L	200	40
70	NDC 70 L	55	11,2	1000	NDC 1000 L	200	44

■ Brass screw connectors
10 - 300 mm²

- Material: CuZn 40 Pb 2 DIN 17660, Screws: DIN 551 steel zinc plated
- Surface: tin plated



Cable Size mm ²	Order Reference	l	number of screws	Cable Size mm ²	Order Reference	l	number of screws
10	NDC 10 SS	30	2	95	NDC 95 SS	55	4
16	NDC 16 SS	40	4	120	NDC 120 SS	55	4
25	NDC 25 SS	45	4	150	NDC 150 SS	60	4
35	NDC 35 SS	45	4	185	NDC 185 SS	60	10
50	NDC 50 SS	48	4	240	NDC 240 SS	65	10
70	NDC 70 SS	52	4	300	NDC 300 SS	65	10

Screws of the screw connectors are for fixation purposes of conductors only. A firm connection needs to be soldered.