



PREMIUM 111

A 7-mil (0,18mm) all weather, premium grade, pressure sensitive vinyl tape which gives excellent performance over a wide range of temperatures. Cold and weather resistant. Flame retardant. Premium 111 can be used as primary insulation for splices at not more than 600 Volts. Use as protective outer jacket over splices and all low temperature applications. UL 510, CSA 22.2 (rated from -18°C to 105°C), ASTM-D-3005, HH-I-595C.

UPC/Cat.	Color	Dimensions	Pkg	Weight
04472	grey	3/4" x .007" x 66' 19mm x 0,18mm x 20m	100/case PP	24lbs 11kg
04453	black	3/4" x .007" x 66' 19mm x 0,18mm x 20m	100/case PP	24lbs 11kg
04478	grey	3/4" x .007" x 20' 19mm x 0,18mm x 6m	40/case C	3lbs 1kg
04447	black	3/4" x .007" x 20' 19mm x 0,18mm x 6m	40/case C	3lbs 1kg



PREMIUM 85 CW

An 8.5 mil (0,21mm) all-weather, premium grade, pressure sensitive vinyl tape that provides heavier thickness for added mechanical and electrical protection. Cold and weather resistant. Flame retardant. Premium 85 CW can be used as primary insulation for splices at not more than 600 Volts. Excellent protective jacket over all types of splices. Excellent cold weather performance. UL 510, CSA 22.2 (rated from -18°C to 105°C), ASTM-D-3005, MIL-I-24391C.

UPC/Cat.	Color	Dimensions	Pkg	Weight
04240	black	3/4" x .0085" x 66' 19mm x 0,21mm x 20m	100/case PP	30lbs 14kg
04252	black	1 1/2" x .0085" x 66' 38mm x 0,21mm x 20m	100/case C	48lbs 22kg
04273	black	1 1/2" x .0085" x 108' 38mm x 0,21mm x 33m	50/case C	38lbs 17kg
04311	black	2" x .0085" x 66' 51mm x 0,21mm x 20m	40/case C	29lbs 13kg
04203	black	3/4" x .0085" x 20' 19mm x 0,21mm x 6m	40/case C	28lbs 13kg



PREMIUM 37 Color Coding

A 7 mil (0,18mm) all weather, premium grade, pressure sensitive vinyl tape that is available in nine colors for color coding. Cold and weather resistant. Flame Retardant. Use Premium 37 for quick identification of electrical circuits, containers, and conduit systems, as well as primary insulation for splices at not more than 600 volts. UL 510, CSA 22.2 (rated from -18°C to 105°C), ASTM-D-3005, HH-I-595C.

UPC/Cat.	Color	Dimensions	Pkg	Weight
03702	green	3/4" x .007" x 66' 19mm x 0,18mm x 20m	20/case PP	5lbs 2kg
03703	yellow	3/4" x .007" x 66' 19mm x 0,18mm x 20m	20/case PP	5lbs 2kg
03704	red	3/4" x .007" x 66' 19mm x 0,18mm x 20m	20/case PP	5lbs 2kg
03705	blue	3/4" x .007" x 66' 19mm x 0,18mm x 20m	20/case PP	5lbs 2kg
03706	white	3/4" x .007" x 66' 19mm x 0,18mm x 20m	20/case PP	5lbs 2kg
03707	brown	3/4" x .007" x 66' 19mm x 0,18mm x 20m	20/case PP	5lbs 2kg
03708	orange	3/4" x .007" x 66' 19mm x 0,18mm x 20m	20/case PP	5lbs 2kg
03709	grey	3/4" x .007" x 66' 19mm x 0,18mm x 20m	20/case PP	5lbs 2kg
03711	violet	3/4" x .007" x 66' 19mm x 0,18mm x 20m	20/case PP	5lbs 2kg
03165	multi-pak*	1/2" x .007" x 20' 12,7mm x 0,18mm x 6m	24-6 paks	8lbs 4kg
03167	green	1/2" x .007" x 20' 12,7mm x 0,18mm x 6m	40/case IB	3lbs 1kg
03168	yellow	1/2" x .007" x 20' 12,7mm x 0,18mm x 6m	40/case IB	3lbs 1kg
03169	red	1/2" x .007" x 20' 12,7mm x 0,18mm x 6m	40/case IB	3lbs 1kg
03170	blue	1/2" x .007" x 20' 12,7mm x 0,18mm x 6m	40/case IB	3lbs 1kg
03171	white	1/2" x .007" x 20' 12,7mm x 0,18mm x 6m	40/case IB	3lbs 1kg
03172	brown	1/2" x .007" x 20' 12,7mm x 0,18mm x 6m	40/case IB	3lbs 1kg
03173	orange	1/2" x .007" x 20' 12,7mm x 0,18mm x 6m	40/case IB	3lbs 1kg
03174	grey	1/2" x .007" x 20' 12,7mm x 0,18mm x 6m	40/case IB	3lbs 1kg
03175	violet	1/2" x .007" x 20' 12,7mm x 0,18mm x 6m	40/case IB	3lbs 1kg

* Multi-pak contains one each: red, blue, white, green, yellow, orange