



122 RUBBER TAPE Splicing Compound

A 30 mil (0,76mm) UL listed, self-amalgamating, low voltage rubber tape which can be used as primary insulation for splices at not more than 600 volts when used in conjunction with a friction or vinyl jacketing tape. UL 510.

UPC/Cat.	Color	Dimensions	Pkg	Weight
02002	black	3/4" x .030" x 22' 19mm x 0,76mm x 6,7m	100/case C	34 lbs 15kg
02020	black	2" x .030" x 22' 51mm x 0,76mm x 6,7m	40/case C	35 lbs 16kg
02004	black	3/4" x .030" x 11' 19mm x 0,76mm x 3,3m	200/case C	38 lbs 17kg



150 ASTM RUBBER TAPE

A 30-mil (0,76 mm) self-amalgamating, low voltage rubber tape that can be used for insulating cable splices through 2kV, in conjunction with a jacketing tape. Compatible with low and high density polyethylene and polypropylene PIC cables plus all rubber and PVC cable elements. 150 ASTM conforms easily and self-amalgamates into a homogenous, void-free mass to provide an effective moisture seal. ASTM-D-4388, Communications Industry Specification 6746

UPC/Cat.	Color	Dimensions	Pkg	Weight
02006	grey	3/4" x .030" x 30' 19mm x 0,76mm x 9m	100/case C	52 lbs 24kg



125 ELECTRICAL FILLER TAPE

A 125 mil (3,2mm) self amalgamating, low voltage insulating compound designed for quick, void-free insulation build-up. 125 can be easily molded by hand to conform to irregular shapes and can be used as primary insulation for splices through 5kV in conjunction with other insulating tapes. 125 is ideal for covering split bolts, padding bus bar edges and connections, and provides an excellent moisture seal. MIL-I-17695A

UPC/Cat.	Color	Dimensions	Pkg	Weight
02074	black	1 1/2" x .125" x 60" 38mm x 3,2mm x 1,5m	10/case B	35 lbs 16kg