



L969 PLYVOLT™ Linerless High Voltage Insulating Tape

A 30-mil (0,76mm) EPR , self-bonding high voltage tape for insulating and jacketing splices through 69kV. L969 Plyvolt is linerless, and permits quicker application than a tape with liner. Yields a void-free build-up. Excellent corona, ozone and chemical resistance. L969 Plyvolt can also be used for building stress-cones on power cable through 35kV. ASTM-D-4388, HH-I-553C.

UPC/Cat.	Dimensions	Pkg	Weight
02211	3/4" x .030" x 30' 19mm x 0,76mm x 9m	100/case B	38 lbs 18kg
02212	1" x .030" x 30' 25mm x 0,76mm x 9m	80/case B	41 lbs 19kg
02213	1 1/2" x .030" x 30' 38mm x 0,76mm x 9m	50/case B	36 lbs 16kg
02214	2" x .030" x 30' 51mm x 0,76mm x 9m	40/case C	37 lbs 17 kg



W963 PLYSAFE® High Voltage Insulating Tape with Liner

A 30-mil (0,76mm) EPR, self-amalgamating high voltage tape for insulating and jacketing splices through 69kV. W963 Plysafe amalgamates quickly, yielding a void-free, electrically stable build-up and is ideal for waterproofing. ASTM-D-4388, HH-I-553C/Grade A, MIL-I-3825B.

UPC/Cat.	Dimensions	Pkg	Weight
02117	3/4" x .030" x 30' 19mm x 0,76mm x 9m	100/case B	46 lbs 21kg
02132	1" x .030" x 30' 25mm x 0,76mm x 9m	80/case B	47 lbs 22kg
02134	1 1/2" x .030" x 30' 38mm x 0,76mm x 9m	50/case B	43 lbs 20kg
02145	2" x .030" x 30' 51mm x 0,76mm x 9m	40/case C	44 lbs 20kg



3 BI-SEAL® High Voltage Insulating Tape with Liner

A polyethylene and ethylene propylene rubber based tape possessing superior electrical, chemical, mechanical and thermal properties. Fuses quickly-yielding a void free, electrically stable build-up. For insulating and jacketing of splices on power cable from 600 Volts through 69kV and for building stress cones and jacketing of terminations on power cable from 600 Volts through 35kV. Available in 20 mil (0,51mm) or 30 mil (0,76mm) thickness. ASTM-D-4388, HH-I-553C.

UPC/Cat.	Dimensions	Pkg	Weight
08051	3/4" x .020" x 30' 19mm x 0,51mm x 9m	100/case B	44 lbs 20kg
08052	1" x .020" x 30' 25mm x 0,51mm x 9m	80/case B	45 lbs 21kg
08053	1 1/2" x .020" x 30' 38mm x 0,51mm x 9m	50/case B	40 lbs 18kg
08054	2" x .020" x 30' 51mm x 0,51mm x 9m	40/case C	41 lbs 19kg
08065	3/4" x .030" x 30' 19mm x 0,76mm x 9m	100/case B	53 lbs 24kg
08066	1" x .030" x 30' 25mm x 0,76mm x 9m	80/case B	54 lbs 25kg
08067	1 1/2" x .030" x 30' 38mm x 0,76mm x 9m	50/case B	52 lbs 24kg
08068	2" x .030" x 30' 51mm x 0,76mm x 9m	40/case C	53 lbs 24kg



W962 High Voltage Insulating Tape With Liner

20-mil (0,51mm) EPR based high voltage tape with superior electrical, chemical, mechanical and thermal properties. For insulating and jacketing of splices on power cable from 600 Volts through 138kV and for building stress cones and jacketing of terminations on power cable from 600 Volts through 35kV. W962 is self-amalgamating. ASTM-D-4388.

UPC/Cat.	Dimensions	Pkg	Weight
08080	3/4" x .020" x 30' 19mm x 0,51mm x 9m	100/case B	44 lbs 20kg
08081	1" x .020" x 30' 25mm x 0,51mm x 9m	80/case B	46 lbs 21kg
08082	1 1/2" x .020" x 30' 38mm x 0,51mm x 9m	50/case B	41 lbs 19kg
08083	2" x .020" x 30' 51mm x 0,51mm x 9m	40/case C	44 lbs 20kg