



20 PLYSIL® Silicone Rubber Tape

A 20 mil (0,51mm) triangular cross-section, self-amalgamating silicone rubber tape used for jacketing high voltage terminations on solid dielectric cable through 69kV. 20 PLYSIL is track and erosion resistant and can be used as primary insulation for high temperature (180°C) applications. ASTM-D-2148, MIL-I-46852A.

UPC/Cat.	Dimensions	Pkg	Weight
03455	1" x .020" x 30' 25mm x 0,51mm x 9m	50/case C	18 lbs 8kg



53 PLYARC® Arc and Fireproofing Tape

A 30 mil (0,76mm) unsupported, elastomeric tape that provides excellent flame and arc protection for all types of cables. When exposed to flame, 53 Plyarc will generate a thermally insulating residue for cable protection. Use on cable conduit where added fire protection is required. Unsupported construction offers excellent flexibility and conformability for easy application.

UPC/Cat.	Dimensions	Pkg	Weight
03817	1 1/2" x .030" x 20' 38mm x 0,76mm x 6m	20/case C	12 lbs 5kg
03819	3" x .030" x 20' 76mm x 0,76mm x 6m	10/case C	12 lbs 5kg

77 PLYGLAS® Pressure Sensitive Glass Cloth Tape

A 7 mil (0,18mm) woven glass fabric tape with a thermosetting rubber based pressure sensitive adhesive used for insulating and protecting high temperature (130°C) connections, such as motor leads and transformer windings. 77 Plyglas has high tensile strength for splice reinforcement and provides excellent tear and abrasion resistance. Use 77 Plyglas to hold down 53 Plyarc and Fireproofing Tape. Comm Spec. 7611, ASTM-D-2754, MIL-I-15126F/GFT.



UPC/Cat.	Dimensions	Pkg	Weight
03451	1/2" x .007" x 66' 13mm x 0,18mm x 20m	50/case B	9 lbs 4kg
03456	3/4" x .007" x 66' 19mm x 0,18mm x 20m	50/case B	12 lbs 5kg
03459	1" x .007" x 108' 25mm x 0,18mm x 33m	20/case B	37 lbs 17kg

60 AND 60A Varnished Cambric Tape

60 and 60A Varnished Cambric Tapes are a fine bias (diagonal) weave cotton cloth coated with an electrical insulating varnish which provides good electrical and mechanical protection. V.C. Tapes are available without adhesive (7 mil [0,18mm] thickness), or with adhesive (10 mil [0,25mm] thickness). Both tapes possess good flexibility to allow tight taping of irregular shapes.



UPC/Cat.	Dimensions	Pkg	Weight
03919 (with adhesive)	3/4" x .010" x 60' 19mm x 0,254mm x 18m	40/case B	10 lbs 4kg
03920 (with adhesive)	1 1/2" x .010" x 108' 38mm x 0,254mm x 33m	24/case B	18 lbs 9kg
03925 (with adhesive)	1" x .010" x 108' 25mm x 0,254mm x 33m	8/case	
03921 (without adhesive)	3/4" x .007" x 60' 19mm x 0,18mm x 18,2m	40/case B	9 lbs 4kg
03922 (without adhesive)	1 1/2" x .007" x 108' 38mm x 0,18mm x 33m	24/case B	16 lbs 7kg
03924 (without adhesive)	1" x .007" x 108' 25mm x 0,18mm x 33m	6/case	4 lbs 2kg