

■ HK 60/22

Hand-operated crimping tool 6 - 300 mm²

- Slim crimping head - ideal when space is critical
- For interchangeable dies, series 22, narrow crimping
- Crimping head rotates 360°, flip top style
- Two stage hydraulics
- Automatic retraction when crimp is complete
- Manual retraction in case of need

Part No.	Crimping force	Crimping range	Stroke	Length	Weight
HK6022	60 kN	6 - 300 mm ²	17 mm	460 mm	3.3 kg

Please ask for dies series 22.

Scope of supply	Part No.
Steel carrying case	MK6022

22
KAWAKE

300 mm²



Accessories:	Part No.
Digital meter for force and pressure measurement	TC1S
Measuring adapter series 22	MA22
Force sensor 70 kN	TF70L

■ HK 120/42

Hand-operated crimping tool 16 - 400 mm²

- For interchangeable dies, series 13, wide crimping
- C-shape crimping head, rotates 360°
- Two stage hydraulics
- Automatic retraction when crimp is complete
- Manual retraction in case of need

Part No.	Crimping force	Crimping range	Stroke	Length	Weight
HK12042	120 kN	16 - 400 mm ²	42 mm	560 mm	5.9 kg

Please ask for dies series 13.

Scope of supply	Part No.
Steel carrying case	MK12042

13
KAWAKE

400 mm²



Accessories:	Part No.
Digital meter for force and pressure measurement	TC1S
Measuring adapter series 13	MA120
Force sensor 130 kN	TF130L

■ HSG 55

Hand-operated hydraulic cutting tool max. cable size 55 mm Ø

- Close cutting head with bolt interlock, rotates 360°, flip top style
- Two stage hydraulics
- Automatic retraction when cut is complete
- Manual retraction in case of need

Part No.	Cutting force	Cutting range	Length	Weight
HSG55	120 kN	max. 55 mm Ø	605 mm	7.3 kg

Scope of supply	Part No.
Steel carrying case	MK55

Cu/Al
Al/St

55 mm Ø



Accessories:	Part No.
Outer, stationary blade	ESG55EF
Inner, moving blade	ESG55ES

■ HSG 85/2

Hand-operated hydraulic cutting tool max. cable size 85 mm Ø

- Close cutting head with bolt interlock, rotates 360°, flip top style
- Two stage hydraulics
- Automatic retraction when cut is complete
- Manual retraction in case of need

Part No.	Cutting force	Cutting range	Length	Weight
HSG85	60 kN	max. 85 mm Ø	677 mm	5.9 kg

Scope of supply	Part No.
Steel carrying case	MK85

Cu/Al

85 mm Ø



Accessories:	Part No.
Outer, stationary blade	ESG85EF1
Inner, moving blade	ESG85ES1