

■ K 22

Crimping tool for interchangeable dies 6 - 300 mm²

- Crimping head rotates 360°, flip top style
- Optimised for cable glands and panel building
- With telescopic handles

22
Klauke

300 mm²



Part No.	Range	Length	Weight
K22	6 - 300 mm ²	stepless 560 - 860 mm	2.5 kg

Please ask for dies series 22.

■ K 100

Hand-operated cutting tool for Cu and Al cables up to 14 mm Ø

- For fine and multi-stranded cable
- Short design

Cu/Al

14 mm Ø



Part No.	Range	Length	Weight
K100	max 14 mm Ø	280 mm	0.55 kg

■ K 106/1

Hand-operated cutting tool for Cu and Al cables up to 32 mm Ø

- For earth, plastic and rubber cables
- One hand operation, high leverage (1-tooth system)

Cu/Al

32 mm Ø



Part No.	Cutting range	Length	Weight
K1061	max 32 mm Ø	250 mm	0.55 kg

■ K 106/2

Hand operated cutting tool for Cu and Al cables up to 52 mm Ø

- For earth, plastic and rubber cables
- One hand operation, high leverage (1-tooth system)

Cu/Al

52 mm Ø



Part No.	Cutting range	Length	Weight
K1062	max 52 mm Ø	280 mm	0.74 kg

■ K 150

Hand operated cutting tool for Cu and Al cables up to 50 mm Ø

- High performance because of specially designed flat blades
- Also for fine stranded conductors e.g. VDE 0295 Class 5
- Two hand operation, excellent leverage

Cu/Al

50 mm Ø



Part No.	Cutting range	Length	Weight
K150	max 50 mm Ø	710 mm	3.0 kg

■ K 101/1

Hand operated cutting tool for Cu and Al cables up to 26 mm Ø

- With interchangeable cutting heads
- Also for fine stranded conductors e.g. VDE 0295 Class 5
- Two hand operation, excellent leverage

Cu/Al

26 mm Ø



Part No.	Cutting range	Length	Weight
K1011	max 26 mm Ø	570 mm	1.8 kg

■ K 101/2

Hand operated cutting tool for Cu and Al cables up to 38 mm Ø

- With interchangeable cutting head
- Also for fine stranded conductors e.g. VDE 0295 Class 5
- Two hand operation, telescopic lever handles

Cu/Al

38 mm Ø



Part No.	Cutting range	Length	Weight
K1012	max 38 mm Ø	930 mm	4.2 kg