

## SP - Spiral tubing

- Flexible spiral tube for fitting of cables, conductors, tubes, wire bundles etc.
- Excellent protection against mechanical wear.



Type	Available as Halogen free	Internal diameter, mm	Internal diameter, inch	Pack unit
SP-08100	No	8	.315	100 m
SP-10100	Yes	10	.394	60 m
SP-15100	Yes	15	.590	40 m
SP-20100	Yes	20	.787	40 m
SP-25100	Yes	25	.984	30 m
SP-30100	Yes	30	1.181	20 m
SP-40100	Yes	40	1.575	10 m
SP-50100	No	50	1.968	4 m

### SPH-1

Snap-into fastener of spiral tube in holed mounting plates. 50 pcs in one bag

## PO/POZ profile



- PO oval marking profile with a diameter range from 1.3 to 28.0 mm (AWG 23 – 7/0).
- Very fast, one hand mounting onto cable or wire.
- POZ: Halogen free material.
- Standard colours are yellow and white. Other colours on request.



Type	Diameter mm Min / Max	Area mm <sup>2</sup>	AWG	Compactdisc		Box	
				Reel PO	PO	POZ	
PO / POZ-01	1.3 / 1.8	~0.25	~23-20	6.0 m	250 m	-	250 m
PO / POZ-02	1.7 / 2.2	~0.5	~20-18	5.0 m	250 m	-	250 m
PO / POZ-03	2.0 / 2.5	~0.75	~18-17	4.5 m	250 m	-	250 m
PO / POZ-04	2.2 / 2.8	~1.0	~17-15	4.5 m	200 m	-	200 m
PO / POZ-05	2.7 / 3.5	~1.5	~15-13	4.0 m	200 m	-	200 m
PO / POZ-06	3.2 / 4.0	~2.5	~13-11	3.5 m	200 m	-	200 m
PO-06Q10	-	-	-	3.5 m	-	100 m	-
PO-068TW	6.8 / 7.0	-	-	4.5 m	50 m	-	-
PO / POZ-07	3.8 / 4.7	~4.0	~11-9	3.5 m	100 m	-	100 m
PO / POZ-08	4.6 / 5.5	~6.0	~9-7	-	100 m	-	100 m
PO / POZ-09	5.6 / 7.0	~10.0	~7-5	-	50 m	-	50 m
PO / POZ-10	6.5 / 8.0	~16.0	~5-3	-	50 m	-	50 m
PO / POZ-11	7.0 / 9.5	~18.0	~4-3	-	-	5x10 m	5x10 m
PO / POZ-12	7.5 / 10.0	~20.0	~4-2	-	-	5x10 m	5x10 m
PO / POZ-14	9.5 / 12.0	~25.0	~1/0	-	-	5x10 m	5x10 m
PO / POZ-16	11.5 / 14.0	~35.0	~1/0-2/0	-	-	2x5 m	2x5 m
PO / POZ-18	13.5 / 16.0	~50.0	~2/0-3/0	-	-	2x5 m	2x5 m
PO / POZ-20	15.5 / 18.0	~70.0	~3/0-4/0	-	-	2x5 m	2x5 m
PO / POZ-22	17.5 / 20.0	~95.0	~4/0	-	-	2x5 m	2x5 m
PO / POZ-24	19.5 / 22.0	~120.0	~4/0-5/0	-	-	2x5 m	2x5 m
PO / POZ-26	21.5 / 24.0	~150.0	~5/0-6/0	-	-	2x5 m	2x5 m
PO / POZ-28	24.0 / 28.0	~185.0	~6/0-7/0	-	-	2x5 m	2x5 m