

PHZ - Heat shrink tubing for printing



- Flexible halogen free heat shrink tubing for marking on site.
- Excellent fire safety characteristics.
- Flexible and easy mounted on cables and wires.
- 2:1 shrink ratio.
- Shrink temperature > 90°C.
- Working temperature -30°C to +105°C.
- Standard colour yellow and white, other colours on request.
- Efficient marking and assembly on site.
- Please contact PARTEX for more information regarding customized multi character marking.



Type	Diameter mm Before / Shrinked		Diameter inches Before / Shrinked		Wall thickness shrinked mm	Mini box	Reel
PHZ20016	1.6	0.8	1/16	1/32	0.43	-	200 m
PHZ20024	2.4	1.2	3/32	3/64	0.51	-	200 m
PHZ20032	3.2	1.6	1/8	1/16	0.51	15 m	200 m
PHZ20048	4.8	2.4	3/16	3/32	0.51	12 m	200 m
PHZ20064	6.4	3.2	1/4	1/8	0.65	12 m	150 m
PHZ20095	9.5	4.7	3/8	3/16	0.65	-	150 m
PHZ20127	12.7	6.4	1/2	1/4	0.65	-	100 m
PHZ20190	19.1	9.5	3/4	3/8	0.77	-	50 m
PHZ20254	25.4	12.7	1	1/2	0.89	-	50 m
PHZ20381	38.1	19.1	1.1/2	3/4	1.00	-	25 m
PHZ20510	50.8	25.4	2	1	1.10	-	25 m

PHL - Heat shrink tubing for insulation



- Not for printing, insulation only.
- Shrink ratio: 2:1.
- Standard colour is black, other colours on request.
- Flame retardent crosslinked Polyolefin.
- UL Approved.
- Voltage 600V.
- Shrink temperature 100°C.
- Working temperature -55°C to +125°C.



Type	Diameter mm Before / Shrinked		Diameter inches Before / Shrinked		Wall thickness shrinked mm	Mini box	Reel
PHL20012	1.2	0.6	3/64	3/128	0.42	20 m	300 m
PHL20016	1.6	0.8	1/16	1/32	0.42	17 m	300 m
PHL20024	2.4	1.2	3/32	3/64	0.47	15 m	150 m
PHL20032	3.2	1.6	1/8	1/16	0.50	15 m	150 m
PHL20048	4.8	2.4	3/16	3/32	0.50	12 m	75 m
PHL20064	6.4	3.2	1/4	1/8	0.64	12 m	60 m
PHL20095	9.5	4.7	3/8	3/16	0.64	8 m	60 m
PHL20127	12.7	6.4	1/2	1/4	0.64	8 m	60 m
PHL20190	19.1	9.5	3/4	3/8	0.77	5 m	60 m
PHL20254	25.4	12.7	1	1/2	0.89	5 m	30 m
PHL20381	38.1	19.1	1.1/2	3/4	1.01	-	30 m
PHL20508	50.8	25.4	2	1	1.15	-	30 m
PHL20762	76.2	38.1	3	1.1/2	1.40	-	15 m
PHL21016	101.6	50.8	4	2	1.40	-	15 m